

SMART LED TUBELIGHT



ECO-FRIENDLY



DURABLE



ECONOMICAL

Product Specification

Model No.	Power (W)	CCT (k)	Lumens(Lm)	Lm/w	CRI	Beam Angle	Size (mm)
BL-1006	6W	3000/4000/6000K	540Lm	90Lm/w	>70	120°	37x21x290mm
BL-1006	12W	3000/4000/6000K	1140Lm	95Lm/w	>70	120°	37x21x570mm
BL-1006	20W	3000/4000/6000K	1900Lm	95Lm/w	>70	120°	37x21x870mm
BL-1006	26W	3000/4000/6000K	2470Lm	95Lm/w	>70	120°	37x21x1180mm

CCT Range WW(3000K) NW (4000K) CW (6000K)

Temperature Characteristic T-ambient 25

Temperature

Operating -20~+40°C
Storage -40~+85°C

Humidity

Operating -20~+40°C
Storage -40~+85°C

Electrical Characteristic

input voltage:AC100~240V 50/60Hz
PF:≥0.93 THD:≤20%
Power Efficiency : ≥ 0.9

Advantages

Maximum efficiency and minimum glare
Quick installation and easy maintenance with middle-out wire.
High-tech optical design
Batten integrated t5 led light can greatly saving labor cost
No UV, No lead, No Mercury

