

OUTDOOR IP65 LED TUBELIGHT









ECONOMICAL

Advantages

Tri-Proof lamp for Ip65 waterproof, dust, corrosion and pressure-proof

One equals to two traditional t8 tube in the same size.

Maximum efficiency and minimum glare

Quick installation and easy maintenance

High-tech optical design

widely use for ambient lighting application

Batten integrated t8 led light can greatly saving labor cost

EMC driver inside

No UV, No lead, No Mercury

Product Specification

| Model No. | Power (W) | CCT (k) | Lumens(Lm) | Lm/w | CRI | Beam Angle | Size (mm) |
|-----------|-----------|-----------------|------------|--------|-----|------------|--------------|
| BL-1008 | 18W | 6000K | 1530Lm | 85Lm/w | >80 | 120° | 51x70x604mm |
| BL-1008 | 36W | 3000/4000/6000K | 3060Lm | 85Lm/w | >80 | 120° | 51x70x1168mm |

CCT Range WW(3000K) NW (4000K) CW (6000K)

■ Temperature Characteristic T-ambient 25

| Tempera | ture | Humidity | Humidity | | | |
|-----------|-----------|-----------|-----------|--|--|--|
| Operating | -20~+40°C | Operating | -20~+40°C | | | |
| Storage | -40~+85°C | Storage | -40~+85°C | | | |

Electrical Characteristic

input voltage:AC100~240V 50/60Hz

 $PF: \ge 0.93 \qquad THD: \le 20\%$ Power Efficiency : ≥ 0.9







